

## **PORTABLE POWER SUPPLY**

**PPS 750** 

Our Portable Power Supply series offers highly versatile and portable power supply solutions, powering equipment or devices in the home or outdoors, convenient and easy to use.

It can also be a critical power source and in the event of an emergency.

Ideal for camping and other activities where power is not available or convenient.

A Portable Power Supply is a reliable portable power source for your lifestyle and safety.



Get a Portable Power Supply and stay powered and entertained everywhere!

#### **APPLICATIONS**















## **RUN TIME (approximate)**

DEVICE		PPS 750
<u>;</u> <b>=</b> {	3W Lighting	230h+
8	MP3 Player Recharges	500X+
	Playstation Recharges	90X+
₽.O	Camera Recharges	160X+
	Smartphone Recharges	70X+
	Tablet Recharges	17X+
口	Laptop Recharges	8X+
<b>②</b>	60W Fan	12h+
<u>(33</u>	TV	7h+
	Mini Bar	15h+
	Tooling Up To 500W	1~1.5h

### **Rugged Construction**

· Reliable performance in harsh conditions.

#### **All-in-one Operation**

 With AC & solar inputs as well as outlets for both AC & DC power, Prime Portable Power can supply numerous loads for extended periods.

#### **Long Life**

 Advanced li-ion cells along with other quality components allow Prime Portable Power to deliver a long service life.

#### Go Anywhere

· Lightweight, compact & reliable.

#### Silent Renewable Energy

• The benefits of a generator without the noise and fuss.

# PRODUCT SPECIFICATIONS Product specifications are subject to change without further notice

ITEM	PPS 750	
BATTERY		
Battery Type	Li-ion battery (NMC)	
Battery Capacity	786 Wh (10.8 V 72.8 Ah)	
Cycle Life	>1500	
INPUT		
AC Wall Charging	12.6 V 7.5 A or 12.6 V 10 A	
Solar Charging	12.5 V ~ 25 V / Max. power up to 125 W	
AC OUTPUT (Pure Sine Wave)		
Total Port	Port (**) 2 × AC ports	
Rated Power	500W	
Pulse Power	2500W	
Voltage/Frequency 230 V/50 Hz		
DC OUTPUT		
USB Port	1 × 5 V 1 A	
	1 × 5 V 2 A	
	1 × 5 V 2.4 A (Fast Charge)	
Cigarette Lighter Socket	1 × 12 V / 60 W (Max. 96 W)	
DC Port	2 × 12 V 2.5 A	
LED LIGHT		
Multi-mode	High Bright (100% power)	
	Normal (50% power)	
	Energy Saving (25% power)	
	Emergency Flash	
	SOS Signal	
GENERAL		
Dimensions (L × W × H)	349 × 160 × 285 mm	
Net Weight	7.5 kg	
Operating Temperature	Discharge Temperature: -10 to 45°C	
	Charge Temperature: 0~45°C	
Certification	RoHS, CE, FCC, RCM, PSE, CEC	

Remark - All technical specifications under testing conditions at 25°C (\*\*) AC Ports note: Universal AC sockets. Takes UK 3 pin, Europe 2 pin, Schuko 2 pin plugs





