



12.8V 1.2KWH

V1.0

S-100A

SERIES AND PARALLEL READY



Low self discharge ✓

High cycle and service life ✓

1C High performance lithium battery ✓

Internal Battery Management System ✓

Excellent high temperature performance ✓

High energy density and conversion efficiency ✓

Can be configured in 12V, 24V, 36V or 48V in series ✓

BMS protects internal cells and ensures smooth operation ✓

Built in protection for over-charge, over-discharge & over-temperature ✓

Compatible with most UPS & Inverters using AGM/VRLA charge setting ✓

Perfect replacement Lithium solution for upgrading your lead acid installation ✓

Can parallel up to 16 batteries in 48V configuration. 4 in series and 4 in parallel ✓

TECHNICAL DATA

ITEM	SPECIFICATIONS
Model	Hubble S-100A
Rated Capacity (5HR)	100 Ah
Nominal Voltage	12.8 V
Discharge Ending Voltage	12V
Charging Limited Voltage	14V
Max. Charging Current	100 A
Max. Continuous Discharging Current	100 A
Cell C Rating	1.0 C
Weight	Approx. 10.5 Kg
Configuration	4 in series with 4 banks in parallel for maximum 16 batteries
Parallel	Parallel connection is up to 4 strings
Dimensions (W x D x H)mm	305mm x 170mm x 220 mm
Maximum DC Limits	Maximum 100 Amp Charge per bank & 100Amp discharge per bank
Cells	1st LiFe Prismatic LiFePO4
Design Life	+/- 15 years
Cycle Life @ 1C	+/- 4 000 Cycles
Certification	CE, UN38.3, GBT31484-2015, GBT31485-2015, GBT31486-2015
Outer Package Material	Black Polypropylene Plastic
Operating Temperature	Charging: 0 to +55°C Discharging: -20 to +55°C Storage: -20 to +55°C
Protection	Electronic Circuit Breaker, BMS Voltage Protection, Under Voltage Protection
IP Rating	IP65

**Due to continuous product improvements specifications are subject to change without prior notice.*



www.hubblelithium.co.za