

HYBRID SERIES

Single Phase

LXP 3-6k

- Single phase/Unbalanced 3-Phase
- Support up to 10pcs in parallel
- Intelligent charge features
 - Weather forecast compensation
 - Update electricity price automatically
 - Economize charging/discharging schedule automatically
- Unique monitoring platform
 - Free APPs on smartphone (Android/iOS) & PC (Web)
- Integrated UPS module
 - On/off grid seamless switching under 20ms
- Wide battery compatible list
- Plug & Play (AC and PV port)

LU POWER^{TEK}



SpecifiCation

INPUT (PV DC)	LXP 3000W	LXP 3600W	LXP 4000W	LXP 4600W	LXP 5000W	LXP 6000W
Max. PV array power(W)	6600	7000	7000	8000	8000	8000
Rated PV input voltage(V)	360					
Number of independent MPPT inputs	2					
PV input voltage range(V)	100-550					
MPPT voltage range(V)	120-500					
Start-up voltage(V)	140					
Max. PV input current per MPPT(A)	13					
Max. PV short-circuit current input per MPPT(A)	20					
Battery						
Compatible battery type	Lithium-ion/Lead-Acid					
Rated battery voltage(V)	48					
Battery voltage range(V)	48-60					
Max. charging voltage(V)	60					
Max. charging/discharging current(A)	66				80	
Max. charging/discharging power(W)	3600				4000	
Force wake up battery from PV function	YES					
Grid						
Rated AC voltage(V)	230					
Rated AC frequency(HZ)	50/60					
Rated AC output current(A)	13	15.6	17.4	20	21.7	26
Rated AC output power(W)	3000	3600	4000	4600	5000	6000
Max. AC input current(A)	31.3	31.3	31.3	34.7	34.7	34.7
Max. AC input power(W)	7200				8000	
PF	0.99(Adjustable from 0.8 leading to 0.8 lagging)					
THDI	<3%					
Rated AC current of BYPASS relays(A)	40					
UPS						
Rated output power with Solar(W)	3000	3600	4000	4600	5000	6000
Rated output power without Solar(W)	3000	3600	4000	4000	4000	4000
Rated output voltage(V)	230					
Rated output current(A)	13	15.6	17.4	17.4	17.4	17.4
Rated output frequency(Hz)	50/60					
Surge power, duration	4500W, 30S					
Switching time(UPS)	20ms					
Wave form	Sine wave					
THDV	<5%					
Efficiency						
Max. MPPT efficiency	99.0%					
Max. efficiency	97.3%					
EU efficiency	97.0%					
Max. charging efficiency	94.5%					
Max. discharging efficiency	94.5%					
Protection						
Over current/voltage protection	YES					
Anti-islanding protection	YES					
AC Short-circuit current protection	YES					
Leakage current protection	YES					
Ground fault monitoring	YES					
Grid monitoring	YES					
DC switch	YES					
DC surge protection Type III	YES					
AC surge protection Type III	YES					
General						
Dimensions(W*H*D)	455*565*181mm/17.9*22.2*7.1inch					
Weight	20kg/44.1lbs					
Ingress protection rating	IP65					
Operating environment temperature range	-25-60°C					
Storage temperature range	-40-65°C					
Relative humidity	0-95%					
Display & Communication interface	LCD, RS485/Wi-Fi/CAN					
Warranty	5 years					
Cooling method	Natural					
Topology	Transformer-less					
Altitude	2000m					
Noise emission(typical)	<25dB					
Standards & Certification						
IEC 62109-1/2, IEC 62040, IEC 62477, EN 61000, IEC 60068, EN 62920, AS4777.2, NRS 097, EN 50549, RD1699, RD413, RD647, UNE 217001, NTS TYPE A, CEIO-21, CEIO-16, VDE-AR-N 4105, UTE C15-712-1/XP C15-712-3/VFR 2019, G98, G99						

Your Reliable Energy Solution Partner

