

# Hybrid Inverter

## SUN-3.6/5K-SG01/03LP1-EU



Colorful touch LCD, IP65 protection degree

6

6 time periods for battery charging/discharging

120

Max. charging/discharging current of 120A

16

Frequency droop control, Max.16pcs parallel



DC couple and AC couple to retrofit existing solar system



Support storing energy from diesel generator

**Deye**

*Clean Power For You*

Model	SUN-3.6K-SG01/03LP1-EU	SUN-5K-SG01/03LP1-EU
<b>Battery Input Data</b>		
Battery Type	Lead-acid or Lithium-ion	
Battery Voltage Range (V)	40~60V	
Max. Charging Current (A)	90A	120A
Max. Discharging Current (A)	90A	120A
Charging Curve	3 Stages / Equalization	
External Temperature Sensor	Optional	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
<b>PV String Input Data</b>		
Max. DC Input Power (W)	4680W	6500W
PV Input Voltage (V)	370V (100V~500V)	
MPPT Range (V)	125~425V	
Full Load DC Voltage Range	240~425V	
Start-up Voltage (V)	150V	
PV Input Current (A)	13A+13A	
No.of MPPT Trackers	2	
No.of Strings Per MPPT Tracker	1+1	
<b>AC Output Data</b>		
Rated AC Output and UPS Power (W)	3600W	5000W
Max. AC Output Power (W)	3960W	5500W
Peak Power (off grid)	2 times of rated power, 10 S	
AC Output Rated Current (A)	15.7A	21.7A
Max. AC Current (A)	18A	25A
Max. Continuous AC Passthrough (A)	35A	
Power Factor	0.8 leading to 0.8 lagging	
Output Frequency and Voltage	50/60Hz; 220/230 / 240Vac (single phase)	
Grid Type	Single Phase	
Current Harmonic Distortion	THD<3% (Linear load<1.5%)	
<b>Efficiency</b>		
Max. Efficiency	97.60%	
Euro Efficiency	96.50%	
MPPT Efficiency	99.90%	
<b>Protection</b>		
PV Input Lightning Protection	Integrated	
Anti-islanding Protection	Integrated	
PV String Input Reverse Polarity Protection	Integrated	
Insulation Resistor Detection	Integrated	
Residual Current Monitoring Unit	Integrated	
Output Over Current Protection	Integrated	
Output Shorted Protection	Integrated	
Output Over Voltage Protection	Integrated	
Surge protection	DC Type II / AC Type II	
<b>Certifications and Standards</b>		
Grid Connection Standard	EN50549-1, CEI 0-21, IEC61727, IEC62116, IEC60068, IEC61683, ABNT NBR 16149, ABNT NBR 16150, AS4777.2, VDE 4105, XP C15-712-3, RD1699, UNE 206006 IN, UNE 206007-1 IN	
Safety EMC / Standard	IEC62040-1, IEC62109-1/-2, IEC61000-6-1, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, IEC61000-4-16, IEC61000-4-18, IEC61000-4-29	
<b>General Data</b>		
Operating Temperature Range (°C)	-25~60°C, >45°C Derating	
Cooling	Smart cooling	
Noise (dB)	<30 dB	
Communication with BMS	RS485; CAN	
Weight (kg)	20.5	
Size (mm)	330W×580H×232D	
Protection Degree	IP65	
Installation Style	Wall-mounted	
Warranty	5 years	