

## 9L GEL LITHIUM BATTERY FIRE EXTINGUISHER



### Product Specification:

▶ <b>PRODUCT CODE :</b>	EGS9
▶ <b>CAPACITY :</b>	9 Litres
▶ <b>MEDIUM :</b>	FIREBLOCK LITHIUM Gel
▶ <b>PROPELLANT :</b>	Nitrogen gas
▶ <b>FILLED &amp; EMPTY WEIGHTS :</b>	Filled 14kg   Empty 4.9kg
▶ <b>NOMINAL DISCHARGE TIME :</b>	49 seconds
▶ <b>OPERATING PRESSURE :</b>	15 bar at 20 °C
▶ <b>TEST PRESSURE :</b>	27 bar
▶ <b>OPERATING TEMP RANGE :</b>	+5°C to +60°C
▶ <b>CYLINDER CONSTRUCTION :</b>	Mild steel
▶ <b>CYLINDER FINISH :</b>	Polyester
▶ <b>VALVE FINISH :</b>	Brass
▶ <b>PACKING SPEC (HxWxD) :</b>	552 x 205 x 205mm

### Product Details:

<b>1</b> Valve	<b>6</b> Hose
<b>2</b> Safety pin	<b>7</b> Cylinder
<b>3</b> Anti-tamper seal	<b>8</b> Hose clip
<b>4</b> Pressure gauge	<b>9</b> Wall bracket
<b>5</b> 9L FIREBLOCK LITHIUM Gel	<b>10</b> Transit tie* (yellow / blue)

### Application Type:

#### Back-up Power and Solar Installations

Typical Battery Capacity Ranges : Up to 5000Wh



JacTone Cylinder FIREBLOCK Lithium Gel



\* Transit tie to be removed on commissioning



552mm

189mm (Cylinder Width)

212mm (Base Width)